

Note: This datasheet may be out of date. Please download the latest datasheet of BLM18BD421SN1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BLM18BD421SN1%23

"#" indicates a package specification code.

BLM18BD421SN1#







< List of part numbers with package codes > BLM18BD421SN1B BLM18BD421SN1D

BLM18BD421SN1J



Appearance & Shape















Applications

Other Usage For general



Packaging Information

		Standard
Packaging	Specifications	Packing
		Quantity
В	Bulk(Bag)	1000
D	180mm Paper Tape	4000
J	330mm Paper Tape	10000



Features

The chip ferrite beads BLM series is designed to work nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted. BLM series is effective in circuits without stable ground lines because BLM series does not need a connection to ground.

BLM B series can minimize attenuation of the signal waveform due to its sharp impedance characteristics. Various impedances are available to match signal frequency.

The nickel barrier structure of the external electrodes provides excellent solder heat resistance.

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





BLM18BD421SN1#

Note: This datasheet may be out of date.

Please download the latest datasheet of BLM18BD421SN1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BLM18BD421SN1%23

"#" indicates a package specification code.



Specifications

Shape	SMD	
Size Code (in inch)	0603	
Length	1.6mm	
Length Tolerance	±0.15mm	
Width	0.8mm	
Width Tolerance	±0.15mm	
Thickness	0.8mm	
Thickness Tolerance	±0.15mm	
Operating Temperature Range	-55°C to 125°C	
Mass(typ.)	0.005g	
Number of Circuit	1	
Rated Current (at 85°C)	250mA	
Rated Current (at 125°C)	250mA	
DC Resistance(max.)	0.55Ω	
Impedance (at 100MHz)	420Ω	
Impedance (at 100MHz) Tolerance	±25%	
Size Code (in mm)	1608	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



BLM18BD421SN1#


Note: This datasheet may be out of date.

Please download the latest datasheet of BLM18BD421SN1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BLM18BD421SN1%23

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

